



OPTIPETTE

single & multichannel pipettes



SCIENCE AT YOUR FINGERTIPS



Ordering information

Model	Cat. no.	Volume (µl)	A(%)	P(%)
OP2	5601	0.2	± 12	± 6.0
		1.0	± 2.7	± 1.3
		Max 2.0	± 1.5	± 0.7
OP10	5602	Min 0.5	± 4.0	± 2.8
		5.0	± 1.0	± 0.6
		Max 10.0	± 0.5	± 0.4
OP20	5603	Min 2	± 3.0	± 1.5
		10	± 1.0	± 0.5
		Max 20	± 0.8	± 0.3
OP100	5604	Min 10	± 1.6	± 0.80
		50	± 0.8	± 0.24
		Max 100	± 0.8	± 0.20
OP200	5605	Min 20	± 1.2	± 0.60
		100	± 0.8	± 0.25
		Max 200	± 0.6	± 0.20
OP1000	5606	Min 100	± 1.6	± 0.40
		500	± 0.7	± 0.20
		Max 1000	± 0.6	± 0.15
OP5000	5608	Min 1000	± 0.6	± 0.25
		2500	± 0.6	± 0.20
		Max 5000	± 0.5	± 0.15
OP10000	5609	Min 1000	± 2.5	± 0.6
		5000	± 0.8	± 0.3
		Max 10000	± 0.5	± 0.2

The OP2 minimum volume is 0.1 µl.

Model	Cat. no.	Volume (µl)	A(%)	P(%)
OP8-10	5141	Min 0.5	± 10	± 8.0
OP12-10	5145	5	± 4.0	± 2.0
		Max 10	± 2.0	± 1.2
OP8-50	5142	Min 5	± 4.0	± 2.5
OP12-50	5146	25	± 3.0	± 1.2
		Max 50	± 1.6	± 0.6
OP8-200	5143	Min 20	± 3.0	± 1.5
OP12-200	5147	100	± 1.5	± 0.8
		Max 200	± 1.0	± 0.6
OP8-300	5144	Min 50	± 1.6	± 1.5
OP12-300	5148	150	± 1.2	± 1.0
		Max 300	± 1.0	± 0.6

More information about OPTIPETTE pipette series and accessories available on the Website: www.htl.com.pl

easy calibration

reduced operating forces

durable & chemically resistant

colour-coded rings

UV resistant body

wide range of accessories

